

OPTIONAL FEATURES FOR MODELS 20/30 & 20/50

DISINFECTANT PACKAGE

HUBSCRUB follows strict industry guidelines for disinfection. In one mode, equipment that is being disinfected will stay in the wash chamber for the full contact time. Equipment in the wash chamber remains in a high humidity environment insuring the disinfectant remains wet for the full time.

In another mode, the disinfectant is sprayed onto the equipment in the last cycle. The operator removes equipment for contact time outside of the unit. This mode substantially increases production when cleaning and disinfecting equipment.

Combining Quick Disinfectant with contact time outside of the unit results in a 2 ½ minute complete cycle. Additionally, water usage is only 3 gallons. Multiple contact times can also be selected for infection control requirements that have claims from 1 to 10 minute contact times.

Disinfection components include; Push button switch that illuminates when disinfection has been selected. Metering pump for dispensing disinfectant. Foam control to minimize suds from disinfectant. Water purge of disinfectant lines to reduce chemical residue. Low chemical sensor to ensure correct dilution ratio. Multiple selections of contact time. Accreditation approved process.

USER SPECIFIED DISINFECTANT

If a user would like to continue with their present disinfectant, we will test their product for chemical compatibility, reprogram our software for dilution changes if required and ensure safeness with HUBSCRUB components.

UNDER SPRAY SYSTEM

The under side of equipment is often neglected when cleaning. Our under spray system uses a recessed high volume spray nozzle to directly clean the underside of equipment and the inside surfaces such as the inner side of wheelchair wheels that are typically not reached.

1HP BOOSTER WASH PUMP

1hp industrial pump produces up to 50 pounds of spray pressure impact through every nozzle to improve cleaning effectiveness for heavily soiled equipment.

MANUAL SPRAY ATTACHMENT

A convenient spray attachment located inside the wash chamber offers multiple cleaning options from complete wash (with detergent) and rinse for miscellaneous equipment or as a pre-spray for heavily soiled equipment prior to the automated process.

GUARD RAILS

Guard rails provide protection for the dual rotating spray arms on each side. Guard rails are highly recommended particularly if multiple operators are using the system.

PARTS CLEANING

Push button switch illuminates when parts cleaning has been selected. Rotating spray system rotates only in the lower region to concentrate cleaning of parts such as foot rests, leg rests, rehab parts, cushions, etc that are contained in a user supplied basket or a HUBSCRUB basket.

PARTS BASKET

Basket accommodates a number of parts. 5" high swivel caster wheels raise the basket off the floor for effective under spray cleaning and the concentrated focus of the rotating spray system.

MAINTAIN HOT WATER

Water temperature is maintained at 110F degrees to insure water stays at recommended temperature when the unit is idle for up to two hours. Heating element is control by the processor and will shut off if sink is empty or the time allocation has exceeded 2 hours without use.

CUSTOM CHEMICAL COUPLINGS

Separate couplings for chemical tubing and container cap provide ease of use and additional safety when replacing empty containers. (Set of five).

CYCLE COUNTER

Every cleaning cycle is counted and displayed through the see-thru window. Counter can be used for production measurement, billing or preventive maintenance schedules.

HUBSCRUB MAT AND TOWEL

A 44" x 96" towel attaches to a similar size vinyl mat with Velcro for easy removing. Mat and towel are placed under door to collect water when the door is opened. Ideal for locations that require control of water and safety concerns in a traffic area. Easy removal of towel for washing and drying.

POWER DRY

The HUBSCRUB Power Dry is designed to cut drying time by as much as 75%. The Power Dry provides gentle heat and high air velocity to help dry equipment quickly and thoroughly. In combination with HUBSCRUB's Drying Aid, drying time is substantially reduced.