

OPTIONS AND ACCESSORIES

Mat and Towel



A vinyl mat on the floor surface and terry cloth towel on top is used to contain drips of water when the door is opened or from equipment when removed. It is 4' wide by 8' long. Both the mat and towel has Velcro sewed in along the sides which can be separated at the end of the day to be dried or washed and dried.

Parts Basket



The parts basket is 11" high X 20" long by 16" wide. Swivel caster wheels are 5 inches high to raise the basket off the floor for the underspray and for mobility convenience. Excellent cleaning is achieved by the underspray system and the rotating spray systems that provide spray pressure to all sides of the parts.

Adjustable Ramps



HUBSCRUB ramps are 4' long and are adjustable side to side. A receiver plate is attached to the base for the ramps to slip into. People that are not familiar with handling wheelchairs and other mobility equipment find the ramps to be easy to load and unload equipment. The ramps extend one foot beyond the door opening. Check your overall distance for the ramps and the equipment that you are placing in the unit.

Parts Rack



Our parts rack is stainless steel and can accommodate 50 + lbs. The rack has six hooks that rest on the guard rails and is very easy to install and remove. The rack measures 30" X 30" providing ample room for all types of parts. This photo shows a small sample of parts. Once again the combination of the underspray system and rotating spray systems provide deep cleaning and disinfection for all sides of the parts.

Power Dry



HUBSCRUB's Power Dry is a small package with Big Performance. For example; a hair dryer has an average air velocity of 40mph. Our Power Dry air velocity is 160mph. A hair dryer has an average of 10cfm, cubic feet per minute while our Power Dry is 85cfm. Great little product and convenient to quickly dry parts or remove water pockets.

Spray Arm Speed Control



Located on the touch screen panel is an adjustment knob that controls the spray systems rotation speed from slow to fast. Also a pause setting that holds the spray systems position in one location while it is spraying. This option is also used with the Part Selection to rotate to a certain height for the parts basket or parts rack. This option is better suited for a service business or to a facility that has a dedicated operator that can take advantage of using the option.

Personal Spray Attachment



The Personal Spray Attachment is very handy and recommended for all models. The attachment is located in the front corner as you open the door so it can be quickly accessed. It can dispense a detergent for washing equipment and also includes a rinse function providing a complete cycle for equipment that does not need the full **HUBSCRUB** cycle, Spray pressure is govern by the facility water pressure. The system does not need power to operate the Spray Attachment.

UNDERSPRAY, PARTS, NO-FOAM



UNDERSPRAY

The optional Underspray system is recommended for all models. Located in the floor grate is a flush mounted wide cone spray nozzle that delivers over 50 lbs of spray pressure with 7+ gallons of recycled water per minute. As the name implies, this option provides high pressure cleaning to the underside of equipment. This option can be turned on or off using the touchscreen pictured above.

PARTS

The optional Parts Selection rotates the spray system only to a certain height that is determined by the optional Spray Arm Speed Control. The purpose of this selection is to concentrate spray pressure only in the parts basket or on the parts rack location. This selection can be turned on or off through the touchscreen.

NO-FOAM

No-Foam selection is used when a chemical liquid creates substantial foaming due to agitation. By selecting this feature, HUBSCRUB's No-Foam would be used to minimize excessive suds. Once selected, the system would draw out of the HUBSCRUB No-foam container less than .5oz into the main sink and thru mixing minimize suds.